

Electronic Supplementary Material – Hydrogeology Journal

Characterization of preferential flow paths between boreholes in fractured rock using a nanoscale zero-valent iron tracer test

Po-Yu Chuang¹, Yeeping Chia^{1*}, Ya-Hsuan Liou¹, Mao-Hua Teng¹, Ching-Yi Liu¹, Tsai-Ping Lee²

¹Department of Geosciences, National Taiwan University, No. 1, Sec. 4, Roosevelt Rd., Taipei 106, Taiwan.

²Sinotech Engineering Consultants, Inc., No. 280, Xinhua 2nd Rd., Taipei 114, Taiwan

*Corresponding author, Yeeping Chia

Phone: + 886 (2) 33665873, e-mail: yipc@ntu.edu.tw

Table S1 Well specifications

Well name	Depth (m)	Drilling date	Drilling method	Core sample depth (m)	Borehole diameter (cm)	Casing diameter (cm)	Casing depth (m)	Overburden thickness (m)
A	25	2011.08	Rotary drilling	0–25	10.16	10.16	0–15.5	13.8
B	25	2011.08	Rotary drilling	0–25	10.16	10.16	0–15	12.7
C	25	2011.08	Rotary drilling	0–25	10.16	10.16	0–15	13.1